

Spring Plungers • long version

22070.0360



Product Description

To be used for ejecting, as a detent, for applying pressure or as a shock element.

Material

Pin

- Stainless Steel 1.4305, nitrided

Body

- Stainless steel 1.4305

Spring

- Stainless steel


Assembly

Spring plungers can be mounted and removed by means of the slot or internal hexagon.

Please use a special assembly tool for mounting with a slot (pin side).

Characteristic

Heavy spring load: marked with two lines



More information

Notes


Special types on request.

Spring plungers are specially tested for spring range and forces.



References

Thread lock: polyamide all-around coating (for details please refer to the technical appendix).

Drawing



Order information

| Dimensions | | | | | | | Stroke s | WS | Spring load ¹⁾ | |  |  | Art. No. | |
|--|----------------|----------------|----------------|----------------|-----|---|-------------|------|---------------------------|----------------|---|---|----------|------------|
| d ₁ | d ₂ | d ₃ | l ₁ | l ₂ | n | t | | | F ₁ | F ₂ | min. | | | max. |
| [mm] | | | | | | | [mm] | [mm] | [N] | | [°C] | [g] | | |
| stainless steel, heavy spring load, with thread lock | | | | | | | | | | | | | | |
| M16 | 8 | 13.4 | 148 | 35 | 3.2 | 3 | 50 | 6 | 13 | 75 | -30 | 90 | 122 | 22070.0360 |

¹⁾ statistical average value

Application example



Compliance

RoHS compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

Does not contain Proposition 65 substances

No Proposition 65 substances included.

<https://www.P65Warnings.ca.gov/>

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.