# Ball Lock Pins • self-locking, with L-handle

22340 0177



# **Product Description**

For quick fastening, locking, adjusting, changing and securing. Quickly and easily unlockable for frequently repeated connections.

All versions are corrosion resistant. When using stainless steel 1.4542: high-strength, hardened, abrasion resistant pin with high load capacity. Version with ergonomic grip.

### **Material**

# Pin part

· Stainless steel 1.4305

#### Handle

Aluminium, black similar to RAL 9005

#### Press button

· Stainless steel, black

# **Spring**

· Stainless steel

# **Operation**

The balls are unlocked by pressing the button.

# Characteristic

Types from stainless steel 1.4542 with marking below the balls.

### More information

### **Notes**

Special types on request.

This product is also available in INCH dimensions.

#### Accessories

Can easily be fitted with retaining cable EH 22400.

# **Further products**

- Locating Bushings, for ball lock pins and socket pins
- Locating Bushings, with flange, for ball lock pins and socket pins
- Retaining Cables
- Positioning Bushings, with collar, DIN 172 A
- Positioning Bushings, without collar, DIN
- Ball Lock Pins with L-handle, single acting comply with NAS / MS17986

# **Drawing**



\*\* Types from stainless steel 1.4542 with marking.

Halder, Inc. www.halder


www.halderusa.com Page 1 of 3
Published on: 7.4.2024


# **Order information**

<b>d</b> <sub>1</sub> -0.04 -0.08	I <sub>1</sub> +0.6	d <sub>2</sub>	d <sub>3</sub>	l <sub>2</sub> ±1	Dimensio	ns I <sub>4</sub>	l <sub>5</sub>	I <sub>6</sub>	l <sub>7</sub>	Location hole H11	min.	max.	ı	Shearing resistance, two-shear <sup>1)</sup> min.	Art. No.
					[mm]		[mm]	[°C]		[g]	[kN]				
Stainle	Stainless steel														
16	45	19	23.4	14	42.2	27.3	67.6	24.7	15.1	16	-30	150	172	155	22340.0177

<sup>1)</sup> Shearing resistance similar to DIN 50141

# **Application example**





Halder, Inc.

www.halderusa.com

# Compliance

# **RoHS** compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

# Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

# **Does not contain Proposition 65 substances**

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

# **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



www.halderusa.com Page 3 of 3

Published on: 7.4.2024