# **Locating Bushings ⋅** for ball lock pins and socket pins

# 22400.0916



## **Product Description**

This design with holes on the front face (picture 2) is suitable for applications which require installation flush to the surface.

Locating bushings are used for quick and safe locating of ball lock pins EH 22340., EH 22350., EH 22370. and EH 22380. and socket pins EH 22400.

Optimised centering due to precise collar (e.g. quick mounting of plates and components). All versions are corrosion and abrasion resistant.

#### Material


• Stainless steel 1.4305

## **Assembly**

This design with holes on the front face (picture 2) can be installed via a cranked pin face wrench or alternatively via a pin faced socket wrench.

Ensure safe tolerances and consistent function. Easily incorporable into different materials. Can be used in thin-walled pieces. Application from both sides.

## **Drawing**




# Order information


Dimensions										ws	I	Art. No.	
d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	I <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	I <sub>4</sub>	I <sub>5</sub>	I <sub>6</sub>		_		
H11		h9											
[mm]										[mm]	[g]		
with oute	with outer hexagon – picture 3												
16	M30	36	19.5	39	29	15.5	23.5	6.1	12.8	24	124	22400.0916	



Halder, Inc. www.halderusa.com

# **Application example**





# Compliance

## **RoHS** compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

#### Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

Halder, Inc.

#### Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

#### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



www.halderusa.com Page 2 of 2

Published on: 7.4.2024