# **Nuts for T-Slots •** DIN 508

# 23010.0163



# **Product Description**

These nuts for T-slots (slot nuts) are manufactured according to DIN 508. The range is extended by other dimensions that are not included in DIN.

### **Material**

· Heat-treated steel, quality 8, bright

### **Assembly**


The entire loading capacity of the T-nut can only be applied if the screwing is guaranteed to be made over the total thread length of the T-nut.


## More information

### Notes

Special types on request.

# **Drawing**







## **Order information**

T-slot size	Dimensions					for T-slots	Testing force	I	Art. No. <sup>1)</sup>
	d	а	е	h	k	DIN 650	to DIN 508		
							min.		
[mm]	[mm]					[mm]	[kN]	[g]	
Heat-treated steel									
16	M12	15.6	25	18	9	16	67	55	23010.0163

<sup>1)</sup> DIN standards do not include these dimensions.

# **Application example**







Halder, Inc.

www.halderusa.com

Published on: 7.4.2024

# Compliance

# **RoHS** compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

## Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

### **Does not contain Proposition 65 substances**

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



www.halderusa.com Page 2 of 2

Published on: 7.4.2024