## Spherical Washers / Conical Seats • DIN 6319 23050.0030



### **Product Description**

Spherical washers / Conical seats are used as washers in a screw connection to compensate non-parallel surfaces.

### **Material**

Spherical washerCase-hardened steel, case-hardened, manganese phosphated

### Assembly


Conical seats form D are to be used only for plain, closed round areas. For larger holes only use form G!


### More information


### **Further products**

- Spherical Washers / Conical Seats, similar to DIN 6319, stainless steel
- Fixture Nuts, DIN 6330 (height 1,5 d)











120°

picture 3





### **Order information**

			Dimen	sions			For pin	For screws	Load	Torque for screwed	Ĭ	Art. No.	
<b>d</b> ₁ H13	d <sub>3</sub>	h <sub>1</sub>	h <sub>2</sub>		₄ with conical seat form G ~	r <sub>1</sub>	d <sub>6</sub>	d <sub>6</sub>	capacity for static load max.	connections <sup>1)</sup> max.			
[mm]							[mm]	[mm]	[kN]	[Nm]	[g]		
spheric	spherical washers from case-hardened steel, form C – picture 1												
31	56	3.6	11.2	19.2	19.7	41	30	M30	269	1355	103	23050.0030	

 $^{1)}$  Torques of screws with standard thread, eventual pre-loads to be considered, coefficient of friction  $\mu_{total}$  0.14.

### Application example





### Compliance

### **RoHS compliant**

Contains lead - compliant according to exceptions 6a / 6b / 6c.

Contains SVHC substances >0,1% w/w Contains lead - SVHC list [REACH] as of 23.01.2024.

### **Contains Proposition 65 substances**

# 

Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

### Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.