# **Adjustable Tension Levers**

24440.0301



# **Product Description**

### **Material**

### Lever

· Steel, blackened

## Inner parts

• Steel, blackened, quality 5.8

#### Ball knob

• Thermosetting plastic PF 31, black, DIN 319

# **Operation**


By lifting the lever the serrations are disengaged. The lever can be positioned by the serrations. On releasing the lever, the serrations are automatically re-engaged.


### More information


#### **Notes**

The threaded portion can be exchanged.

# **Drawing**







## **Order information**

Dimensions										I	Art. No.
d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	I	t		
								~	min.		
[mm]										[9]	
with female thread – picture 1, Steel											
											24440.0301

## Compliance

## **RoHS** compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

# Contains SVHC substances >0,1% w/w

Contains lead - SVHC list [REACH] as of 23.01.2024.

# **Contains Proposition 65 substances**



Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

# **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



Halder, Inc.

www.halderusa.com