# **Adjustable Tension Levers**

24440.0328



## **Product Description**

### **Material**

### Lever

· Steel, blackened

### Inner parts

• Steel, blackened, quality 5.8

#### Screw

· Steel, blackened, quality 5.8

## Ball knob

• Thermosetting plastic PF 31, black, DIN 319

## **Operation**


By lifting the lever the serrations are disengaged. The lever can be positioned by the serrations. On releasing the lever, the serrations are automatically re-engaged.


### More information


#### **Notes**

The threaded portion can be exchanged.

## **Drawing**







## Order information

Dimensions										-	Art. No.
d <sub>1</sub>	d <sub>2</sub>	I <sub>1</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	l ~	_	
[mm]											
										[9]	
with screw	/ – picture 2, S	teel								101	

## Compliance

### **RoHS** compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

### Contains SVHC substances >0,1% w/w

Contains lead - SVHC list [REACH] as of 23.01.2024.

### **Contains Proposition 65 substances**



Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



Halder, Inc.

www.halderusa.com