Rubber Endstop Buffers · low structure 25150.1164



Product Description


For elastic, damping, and noise-reducing bearings. They also protect the surfaces. The rubber endstop buffers can also be used as spacers and foot ends. Hardness is $70 \pm 5^{\circ}$ Shore A.


Material

Support washer

- Steel, zinc-plated by galvanization,
- passivated
- Body
- NBR

Drawing









picture 2

Order information

Dimensions						Spring rate R	Load capacity	Spring range	ß		Ĭ	Art. No.
d ₁	h	d ₂ +0.5	d ₃ +0.5	s ₁	S ₂		max.		min.	max.		
[mm]						[N/mm]	[N]	[mm]	[°C]		[g]	
with through-bore – picture 1												
64	5	6	11	2.5	1.1	1460	1460	1	-30	120	66	25150.1164

Application example





Compliance

RoHS compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

Contains SVHC substances >0,1% w/w Contains lead - SVHC list [REACH] as of 23.01.2024.

Contains Proposition 65 substances

Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.

