Rubber Endstop Buffers • low structure

25150 1165



Product Description

For elastic, damping, and noise-reducing bearings. They also protect the surfaces. The rubber endstop buffers can also be used as spacers and foot ends. Hardness is 70 $\pm 5^{\circ}$ Shore A.

Material


Support washer

Steel, zinc-plated by galvanization, passivated


Body

NBR

Drawing









picture 2

Order information

Dimensions						Spring rate R	Load capacity max.	Spring range			I	Art. No.
d₁	h	d ₂ +0.5	d ₃ +0.5	s ₁	S ₂				min.	max.		
[mm]						[N/mm]	[N]	[mm]	[°C]		[g]	
with through-bore – picture 1												
64	13	6	11	2.5	1.1	2016	6050	3	-30	120	95	25150.1165

Application example







Halder, Inc. www.halderusa.com

Compliance

RoHS compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

Contains SVHC substances >0,1% w/w

Contains lead - SVHC list [REACH] as of 23.01.2024.

Contains Proposition 65 substances



Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



Halder, Inc.

www.halderusa.com Page 2 of 2

Published on: 4.2.2024