# **Self-Aligning Pads** • with hard metal ball, ribbed and self-resetting EH 22731.





## **Product Description**

Especially designed for cast parts (hard casting crust). To be used as support, thrust pad and for build into clamping elements.

By resetting to the parallel position the contact point of the self-aligning pad provides a defined initial position, thus preventing the pad clamping in an oblique position when inserting the workpiece.

#### **Material**


## Spring element

• Thermoplastic PUR

· Hard metal, ribbed, nickel-plated

- · Heat-treated steel, tempered, phosphated
- · Stainless steel 1.4057, heat-treated

# **Drawing**





## **Order information**


Dimensions						ws	Load capacity	Tightening torque	-	Art. No.
d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	l <sub>1</sub> ±0.2	l <sub>2</sub> -0.5	Ball diameter		for static load max.	max.		71111101
[mm]						[mm]	[kN]	[Nm]	[g]	
with male thread, flat-faced ball, bearing surface ribbed, Heat-treated steel										
13	М 6	8.3	13	8	10	11	10	10	14	22731.0362
13	M 8	8.3	13	8	10	11	10	25	15	22731.0363
20	M 8	13.2	18	10	16	17	25	25	48	22731.0378
20	M10	13.2	18	10	16	17	25	46	50	22731.0379
20	M12	13.2	18	12	16	17	25	82	53	22731.0380
30	M16	20.0	27	16	25	27	90	206	186	22731.0381
50	M20	34.5	35	20	40	41	165	407	639	22731.0382
50	M24	34.5	35	24	40	41	165	698	673	22731.0383
with male thread, flat-faced ball, bearing surface ribbed, Stainless steel										
13	М 6	8.3	13	8	10	11	10	10	14	22731.0390
13	M 8	8.3	13	8	10	11	10	25	15	22731.0392
20	M 8	13.2	18	10	16	17	25	25	48	22731.0394
20	M10	13.2	18	10	16	17	25	46	50	22731.0396
20	M12	13.2	18	12	16	17	25	82	53	22731.0398
30	M16	20.0	27	16	25	27	90	206	186	22731.0399
50	M20	34.5	35	20	40	41	165	407	639	22731.0400
50	M24	34.5	35	24	40	41	165	698	673	22731.0401



Halder, Inc. www.halderusa.com Page 1 of 2

Published on: 7.4.2024

# **Application example**



# Compliance

## **RoHS** compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

## Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

## Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

## **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



Halder, Inc.

www.halderusa.com Page 2 of 2

Published on: 7.4.2024