

Lateral Plungers • with thread, without seal

22150.0319



Product Description

To be used for positioning and applying pressure, e.g. during painting and sandblasting.

Material

Body

- Steel, zinc-plated by galvanization

Spring

- Steel, blackened

Pin

- Steel, case-hardened, zinc-plated by galvanization

Assembly

Lateral plungers are installed by screwing in by means of a mounting tool.

Formula for calculating the center distance for the mounting hole:

$$l_0 = z/2 + w + x,$$

l_0 = center distance,

y = workpiece height,

w = workpiece length,

x = coordinate dimension,

s = stroke,

z = stop diameter

Calculation dimension x :

y greater than or equal to $l_2 - d_2/2$,

then $x = d_2/2 - s$

or

y smaller than $l_2 - d_2/2$,

then $x = d_2/2 - s - [(l_2 - d_2/2 - y) * 0,123]$



Characteristic

Version standard spring load = spring from steel, blackened

Drawing





Order information

| d ₁ | l ₁ -2 | Dimensions | | d ₂ | l ₂ | Stroke s | WS |  max. |  | Art. No. |
|---------------------------------|----------------------|---|--|----------------|----------------|-------------|------|---|---|------------|
| | | Spring load F max. ¹⁾ ~ | | | | | | | | |
| [mm] | | [N] | | [mm] | | [mm] | [mm] | [°C] | [g] | |
| Pin: Steel/Standard spring load | | | | | | | | | | |
| M12 | 26.5 | 50 | | 5 | 6.4 | 1.6 | 10 | 250 | 8.3 | 22150.0319 |

¹⁾ statistical average value

Accessories

| | Dimensions | |  | Art. No. |
|---|----------------|--|---|------------|
| | d ₁ | | | |
| | [mm] | | [g] | |
| assembly tool | | | | |
|  | M12 | | 76 | 22150.0820 |

Application example



Compliance

RoHS compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

Contains SVHC substances >0,1% w/w

Contains lead - SVHC list [REACH] as of 23.01.2024.

Contains Proposition 65 substances

Lead can cause cancer and reproductive harm from exposure
<https://www.P65Warnings.ca.gov/>

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.