# **Pins**

# 22690.0263



# **Product Description**

To be used as seats, stops and thrust pads.

#### Material


• Steel, case-hardened, blackened

### More information


#### **Further products**

- Seating Pins, ribbed or pointedPins, with plastic bearing surface


## **Drawing**









picture 2




picture 3



picture 4



picture 5




### **Order information**

$\begin{array}{c ccccccccccccccccccccccccccccccccccc$					ws	Tightening torque max.	ă	Art. No.
[mm]					[mm]	[Nm]	[9]	
with male thread, bearing surface ribbed – picture 3								
25	M24	46	41	29	41	498	338	22690.0263



### **Application example**



### Compliance

### **RoHS** compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

#### Contains SVHC substances >0,1% w/w

Contains lead - SVHC list [REACH] as of 23.01.2024.

#### **Contains Proposition 65 substances**



Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

Halder, Inc.

### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



www.halderusa.com Page 2 of 2

Published on: 4.2.2024