# **Ball Casters** • screwable, plain bearing 22752.0666



## **Product Description**

For positioning and aligning of workpieces.

Because of the slide bearing, the ball can roll permanently, and the surface of the workpiece is

At temperatures > 20°C, the carrying figure decreases linearly. (Example: at 90°C the load bearing capacity is max. 60%)

#### Material

### **Bearing**

· plastic

#### Ball

· Stainless steel, hardened

#### Screw


· Stainless steel 1.4305

## More information

#### **Notes**

Special types on request.


## **Drawing**



## **Order information**

d <sub>1</sub>	Dimensions		ws	Static carrying figure C <sub>0</sub>	Tightening torque max.	min.	max.	Ĭ	Art. No.
[mm]			[mm]	[N]	[Nm]	[°C]		[g]	
Stainless steel									
M16	50	8.5	3	1986	3.21	-50	90	58	22752.0666

# **Application example**





Halder, Inc.

www.halderusa.com

## Compliance

## **RoHS** compliant

Compliant according to Directive 2011/65/EU and Directive 2015/863.

## Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

### **Does not contain Proposition 65 substances**

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



Halder, Inc. www.halderusa.com Page 2 of 2

Published on: 4.2.2024