# Expander® Sealing Plugs • with pull-anchor 22880.0304



## **Product Description**

Expander® sealing plugs are used for safe, quick and economic sealing of bore holes in fluid technology, e.g. hydraulic drilling holes in jig and fixture construction. When using sealing plugs with pull-anchor, assembly is made by means of user friendly assembly devices. Body and pin are pre-assembled and suitable for automated processing.

Please refer to the technical data following these product information pages.

#### Material

#### Body

· Case-hardened steel, annealed

# Pin


Steel


## More information

## **Further products**

 Assembly Tools, for Expander<sup>®</sup> sealing plugs with pull-anchor

## **Drawing**






## **Order information**

|                | -              | Art. No.                |                |                |            |            |     |            |
|----------------|----------------|-------------------------|----------------|----------------|------------|------------|-----|------------|
| d <sub>1</sub> | d <sub>2</sub> | <b>d₃</b><br>+0.12<br>0 | I <sub>1</sub> | l <sub>2</sub> | I₃<br>max. | I₄<br>max. | _   |            |
|                | [g]            |                         |                |                |            |            |     |            |
| 4              | 2.5            | 4                       | 4.5            | 39             | 6.5        | 9          | 1.7 | 22880.0304 |

## **Application example**



| Working and control pressures for Expander® sealing plug with pull-anchor |                      |                 |                   |                    |                   |                    |                     |  |  |  |  |
|---|----------------------|-----------------|-------------------|--------------------|-------------------|--------------------|---------------------|--|--|--|--|
| basic material  | ETG-100<br>AISI 1144 | C15Pb<br>1.0403 | GG-25<br>DIN 1691 | GGG-50<br>DIN 1693 | AlCuMg2<br>3.1354 | AlMgSiPb<br>3.0615 | G-AlSi7Mg<br>3.2371 |  |  |  |  |
|   | p [bar]              |                 |                   |                    |                   |                    |                     |  |  |  |  |
| d <sub>1</sub>  | 500                  | 500             | 500               | 500                | 500               | 450                | 450                 |  |  |  |  |
| 4-10 mm   | pTest [bar]          |                 |                   |                    |                   |                    |                     |  |  |  |  |
|   | 1600                 | 1600            | 1600              | 1600               | 1600              | 1400               | 1400                |  |  |  |  |

# Compliance

# **RoHS** compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

## Contains SVHC substances >0,1% w/w

Contains lead - SVHC list [REACH] as of 23.01.2024.

## **Contains Proposition 65 substances**



Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

#### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



Halder, Inc. www.halderusa.com Page 2 of 2

Published on: 4.2.2024