# Swing Bolts • DIN 444, form B 22980.0405



## **Product Description**

Swing bolts similar to DIN 444 however, steel design with higher quality 8.8. The stainless steel A2-50 design has a tensile strength of min. 500 N/mm<sup>2</sup>.

## Material

Stainless steel 1.4301

## More information

#### Notes

Special types on request.


#### References

For torques please refer to appendix - Technical Data -

#### **Further products**

• Swing Bolts, DIN 444, form B, quality 8.8 high precision design

## Drawing



## **Order information**

Dimensions						<b>I</b>	Art. No.
d <sub>1</sub>	I	<b>d₂</b> H9	d <sub>3</sub>	b	s	-	
[mm]						[9]	
Stainless steel							
M5	40	5	12	16	6	7.9	22980.0405

## Compliance

#### **RoHS compliant**

Compliant according to Directive 2011/65/EU and Directive 2015/863.

# Does not contain SVHC substances

No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 23.01.2024.

# Does not contain Proposition 65 substances

No Proposition 65 substances included. https://www.P65Warnings.ca.gov/

#### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.